









Montana ULTRA WIDE 750ml professional urban calligraphy tool



THE NEW MONTANA ULTRA WIDE 750ML

The newest member to arrive in the Montana Cans family is the 750ml ULTRA WIDE can. An ideal tool for contemporary urban calligraphy and ultra wide line work, the ULTRA WIDE can comes in Chrome and Black with a spray width variation from 15cm if applied rapidly at close range, to apx. 60cm if applied slower at a greater distance to the desired surface. Complimented by a specially developed yellow Ultra Wide calligraphy spray cap which is set in a horizontal spray position, users are able to maximize vertical stroke application and achieve a higher vertical spray reach of upto 2m higher then final stroke height. Maximum output can be achieved with Montana ULTRA WIDE CHROME. Due to high pressure beware of wide output and counterstroke! Surface area can be covered in exceptionally fast time. Do not spray near any electrical power sources!







WWW.MONTANA-CANS.COM

GENERAL INFORMATION:

Manan

Montana ULTRA WIDE 750ml professional urban calligraphy tool

product name Montana ULTRA WIDE 750ml color assortment Chrome Black applicable on almost any surface valve system special male valve system Made in GERMANY CHARACTERISTICS pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) Safety conforms to ASTM D-4236 Manufactorer's Certificates ISO 14001:2004, ISO 9001:2008, ISO 14001:2004			
applicable on almost any surface valve system special male valve system Made in GERMANY CHARACTERISTICS pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE 0F WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	product name	Montana ULTRA WIDE 750ml	
valve system special male valve system Made in GERMANY CHARACTERISTICS pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	color assortment	Chrome Black	
Made in GERMANY CHARACTERISTICS pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	applicable on	almost any surface	
CHARACTERISTICS pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety Safety conforms to ASTM D-4236	valve system	special male valve system	
pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE 0F WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	Made in	GERMANY	
pressure level Ultra High-pressure spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236			
spray width min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT! spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	CHARACTERISTICS		
spray distance apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) apply slowly at a greater distance (approx. 1,2m) for max. spray width (60cm) apply rapidly at close range (30cm) for thinner lines (15cm) SAFETY: Safety conforms to ASTM D-4236	pressure level	Ultra High-pressure	
SAFETY: Safety conforms to ASTM D-4236 conforms to ASTM D-4236	spray width	min. 15cm / max 60cm / BEWARE OF WIDE OUTPUT!	DERDATLY FLAMMABLE. UN CK IS DROWSINESS, DR2211 For passe un dyness or chan res. Sube can for 3 ms.
Safety conforms to ASTM D-4236	spray distance		the period ball to be the man evidante la traduitar, en vertante la traduitar, en vertante data vertante des functions de palante construiter dest, traduitar, manter de service de service construiter dest, traduitar y manterio de pala de service construiter de pala de service construiter de palante construiter de palanter construiter de palanter construiter construiter de palanter construiter constr
Safety conforms to ASTM D-4236	CAFETV.		tink dratog af period. Gre or os with girenty of water had with age amount of had extenses. He SWALLOW VCT CONTAINS: Acrosme Ibn berg wormace, Do Nor
a series and a series of the s	SAFETT.		Service States (MSCS) for Service WCP OVPLI Grabit - 1 Berth America: 800-424 School begande Service
Manufactorer's Certificates ISO 14001:2004, ISO 9001:2008, ISO 14001:2004	Safety	conforms to ASTM D-4236	In Construction and and a second application of the Database for a second application of the Database for a second application of the second applica
	Manufactorer's Certificates	ISO 14001:2004, ISO 9001:2008, ISO 14001:2004	Construction of a registration of a registrat
			A set of the set of th

PACKAGING/ LABELING:

container dimension	diameter: 65mm / height: 320mm (without cap)
content/ weight	750ml/ 590g/ NET / 21 OZ.
Identification marking	Extremely flammable, harmful

RECOMMENDED EQUIPMENT:

spray cap	yellow ULTRA WIDE Cap for male valve system	
protection	Montana black latex gloves, respirator	